

**IRWIN**Environmental
Construction
Maintenance

BORING LOG

DRILL RIG:

CME-75

DATE DRILLED:

12-7-93

LOGGED BY:

KELLY
WINTERS

BORING DIAMETER:

11"

BORING NUMBER:

MW9

42111 Avenida Alvarado,
Temecula, California 92590

SAMPLE		DEPTH	WELL	ELEV	SOIL	DESCRIPTION AND REMARKS
TYPE	BLOW COUNT	FEET	CONST.	FEET	TYPE	
						ASPHALT
					SM	
■	6-8-10	5				SILTY SAND: dark brown, very fine, subrounded grains slightly damp, slight to medium plasticity, medium dense, some silt and clay, no odor, OVA 0 ppm
■	5-7-7	10				SILTY SAND: as above, OVA 0 ppm
■	6-7-9	15				SILTY SAND: as above, OVA 0 ppm
■	6-8-8	20				SILTY SAND: as above, OVA 0 ppm
■	6-8-10	25				SILTY SAND: as above, wet, OVA 0 ppm
		30				
		35				
		40				
						Total well depth approximately 40 feet bgs.

COMPLETION NOTES:

4" SCH. 40 PVC 0.02" SLOTTED CASING FROM 40 TO 15 FEET
4" SCH. 40 PVC BLANK CASING FROM 15 FEET BGS TO
GROUND SURFACE. #3 MONTEREY SAND FROM 40 TO 13 FEET
BGS. HYDRATED BENTONITE CHIPS FROM 13 TO 2 FEET BGS.
CONCRETE AND TRAFFIC RATED WELL COVER FROM 2 FEET
BGS TO GROUND SURFACE.

SITE:

MOBIL STATION #18-HE1
1465 SOUTH MAIN STREET
SANTA ANA, CALIFORNIA

PROJECT NO.

29519.00

PAGE 1 OF 1